

Schedule D: Surface Water[^] Quality Targets

Schedule D is a component of Part II - the Regional Plan.

SCHEDULE D INDEX:

Tables	Page Numbers
Table D.1A: Region-wide <i>Water[^]</i> Quality Targets that apply to all <i>Rivers[^]</i>	<u>D-2</u>
Table D.2A: <i>Water[^]</i> Quality Targets for <i>Rivers[^]</i> in each <i>Water Management Sub-zone[*]</i> (<i>WMSZ[*]</i>)	<u>D-3 to D-11</u>
Table D.3A: Additional <i>Water[^]</i> Quality Targets that apply 1 May to 30 September (inclusive) to all Specified Sites/Reaches of <i>Rivers[^]</i> with a <u>Trout Spawning (TS) Value</u>	<u>D-12</u>
Table D.4A: <i>Lake[^] Water[^]</i> Quality Targets	<u>D-16</u>
Table D.5A: <i>Water[^]</i> Quality Targets Key (fold-out)	<u>D-17</u>

USER GUIDE: How to use the contents of Schedule D

Step 1: Identify the *WMSZ^{*}* for your proposed activity (go to Schedule AA)

Step 2: Check if Trout Spawning is a Value for your *WMSZ^{*}* (go to Schedule AB)

Step 3: Identify which targets apply to your activity using steps a to c:

- a. A river[^]:
 - i. Turn first to Table D.1A to see the targets that apply to all *rivers[^]* in the Region
 - ii. Then turn to Table D.2A to see the targets that apply to *rivers[^]* in your *WMSZ^{*}*
 - iii. If the *river[^]* at the *site^{*}* of your proposed activity has the Schedule AB Value of Trout Spawning, turn to Table D.3A to see additional targets that apply 1 May to 30 September (inclusive).

- b. A lake[^]:
 - i. Turn to Schedule E Table E.2(b) to determine if your type of *lake[^]* is referred to in v to vii
 - ii. If your type of *lake[^]* is not referred to in Schedule E Table E.2(b) v to vii then turn to Table D.4A
 - iii. Determine if the *lake[^]* meets the description of a “deep” or “shallow” *lake[^]* from Table D.4A and see the targets that apply to the *lake[^] water[^]* in Table D.4A.

- c. *Water[^]* in the *coastal marine area[^]*:
 - i. Turn to Tables H.4 to H.7 in Schedule H to see the targets that apply in the *coastal marine area[^]*.

USER NOTE: For table abbreviations – please refer to the fold-out **TARGETS KEY** at the back of this schedule.

Additional Water quality standards

Additional standards applying to all natural stream and river waters:

1. The concentration of *Escherichia coli* when the river or stream flow is at or below median flow shall not exceed 260 per 100 millilitres. This standard applies during the period 1st November to 30th April inclusive, and
2. The concentration of *Escherichia coli* when the river or stream flow is at or below three times median flow shall not exceed 550 per 100 millilitres. This standard applies year round.
3. The concentration of toxins due to cyanobacteria (blue green algae) shall not exceed 20 milligrams per cubic metre. This standard applies year round.

Table D.1A: Region-wide Water[^] Quality Targets that apply to all Rivers[^]						
<u>Water Management Zone*</u>	<u>Sub-zone*</u>	<u>E. coli / 100 ml</u>		<u>Periphyton Filamentous Cover</u>	<u>Diatom or Cyanobacterial Cover</u>	<u>QMCI %Δ¹</u>
		<u>< 50th %ile</u>	<u>< 20th%ile</u>			
<u>All Water Management Zones*</u>	<u>All Water Management Sub-zones*</u>	<u>260</u>	<u>550</u>	<u>30%</u>	<u>60%</u>	<u>20</u>

[Formerly POP at D-88]

¹ This target is only relevant for measuring the percentage of change in Quantitative Macroinvertebrate Community Index (QMCI) between appropriately matched habitats upstream and downstream of activities, such as discharges[^] to water[^], for the purposes of measuring the effect of discharges[^] on aquatic macroinvertebrate communities. It is not an appropriate target for the measurement of the general state of macroinvertebrate communities in each Water Management Sub-zone*.

Table D.17: Water quality standards for rivers and streams in each Water Management Sub-zone (Note: refer to and for water quality standards applying to rivers and streams flowing into natural lakes)

Table D.2A: <i>Water</i> [^] Quality Targets for <i>Rivers</i> [^] in each <i>Water Management Sub-zone</i> [*] (Note: refer to Table D.4A for the <i>water</i> [^] quality targets that apply to <i>lakes</i> [^])																						
<i>Water Management Zone</i> [*]	<i>Sub-zone</i> [*]	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (µg/m ³)	SIN (µg/m ³)	QMCI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2-m	<-m	<-3-m	Δ	< 50 th %ile	%Δ
Upper Manawatu (Mana_1)	Upper Manawatu (Mana_1a)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	467 0.167	6 120	400 0.400	2.1	99	4		45	20	3	20
	Mangatewainui (Mana_1b)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	467 0.167	6 120	400 0.400	2.1	99	4		45	20	3	20
	Mangatoro (Mana_1c)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	440 0.110	6 120	400 0.400	2.1	99	4		20	20	3	20
Weber-Tamaki (Mana_2)	Weber-Tamaki (Mana_2a)	7 to 8.5	0.5	19	2	80	4 1.5	2.5 5	120	30	40 0.010	444 0.444	6 120	400 0.400	2.1	99	4		45	20	3	20
	Mangatera (Mana_2b)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	99			45	30	2.5	30
Upper Tamaki (Mana_3)	Upper Tamaki (Mana_3)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99			5	20	3	20
Upper Kumeti (Mana_4)	Upper Kumeti (Mana_4)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99			5	20	3	20
Tamaki-Hopelands (Mana_5)	Tamaki-Hopelands (Mana_5a)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	444 0.444	6 120	400 0.400	2.1	99	4		45	20	3	20
	Lower Tamaki (Mana_5b)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	99			45	30	2.5	30
	Lower Kumeti (Mana_5c)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	99			45	30	2.5	30
	Oruakeretaki (Mana_5d)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	99			45	30	2.5	30
	Raparapawai (Mana_5e)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	99			45	30	2.5	30
Hopelands-Tiraumea (Mana_6)	Hopelands-Tiraumea (Mana_6)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	444 0.444	6 120	400 0.400	2.1	99	4		45	20	3	20
Tiraumea (Mana_7)	Upper Tiraumea (Mana_7a)	7 to 8.5	0.5	23	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5	20		30	2	30
	Lower Tiraumea (Mana_7b)	7 to 8.5	0.5	23	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5	20		30	2	30

Table D.2A: Water Quality Targets for Rivers in each Water Management Sub-zone* (Note: refer to Table D.4A for the water quality targets that apply to lakes)

Water Management Zone*	Sub-zone*	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	QMCI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 m	Δ	< 50 th %ile	%Δ
	Mangaone River (Mana_7c)	7 to 8.5	0.5	23	3	70	2	5	200	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95		20		30	1.6	30
	Makuri (Mana_7d)	7 to 8.5	0.5	19	2	80	4 1.5	2.5 5	120	30	40 0.010	444 0.110	5 120	400 0.400	2.1	99	4		45	20	3	20
	Mangaramarama (Mana_8e)	7 to 8.5	0.5	22	3	70	2	5	200	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95		20		30	1.6	30
Mangatainoka (Mana_8)	Upper Mangatainoka (Mana_8a)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	4		5	20	3	20
	Middle Mangatainoka (Mana_8b)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	444 0.444	6 120	400 0.400	2.1	99	4		45	20	3	20
	Lower Mangatainoka (Mana_8c)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	444 0.444	6 120	400 0.400	2.1	99	4		45	20	3	20
	Makakahi (Mana_8d)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	444 0.444	6 120	400 0.400	2.1	99	4		45	20	3	20
	Mangaramarama (Mana_8e)	7 to 8.5	0.5	22	3	70	2	5	200	30	40	444	5	400		95		20		30		30
Upper Gorge (Mana_9)	Upper Gorge (Mana_9a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Mangapapa (Mana_9b)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
	Mangaatua (Mana_9c)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
	Upper Mangahao (Mana_9d)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	167 0.167	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Lower Mangahao (Mana_9e)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
Middle Manawatu (Mana_10)	Middle Manawatu (Mana_10a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Upper Pohangina (Mana_10b)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50 120	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20

Table D.2A: Water Quality Targets for Rivers in each Water Management Sub-zone* (Note: refer to Table D.4A for the water quality targets that apply to lakes)

Water Management Zone*	Sub-zone*	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	QICI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chla Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 xm	Δ	< 50 th %ile	%Δ
	Middle Pohangina (Mana_10c)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	440 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Lower Pohangina (Mana_10d)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	440 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Aokautere (Mana_10e)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	440 0.110	5 100	400 0.400	2.1	95			45	30	2.5	30
Lower Manawatu (Mana_11)	Lower Manawatu (Mana_11a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Turitea (Mana_11b)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Kahuterawa (Mana_11c)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Upper Mangaone Stream (Mana_11d)	7 to 8.5	0.5	24	3	60	2	5	200	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
	Lower Mangaone Stream (Mana_11e)	7 to 8.5	0.5	24	3	60	2	5	200	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
	Main Drain (Mana_11f)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
Oroua (Mana_12)	Upper Oroua (Mana_12a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	467 0.167	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Middle Oroua (Mana_12b)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Lower Oroua (Mana_12c)	7 to 8.5	0.5	24	3	70	2	5	200	30	45 0.015	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Kiwitea (Mana_12d)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	467 0.167	5 100	400 0.400	2.1	95			45	30	2.5	30
	Makino (Mana_12e)	7 to 8.5	0.5	24	3	70	2	5	120	30	45 0.015	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
Coastal Manawatu (Mana_13)	Coastal Manawatu (Mana_13a)	7 to 8.5	0.5	24	3	70	2	5	200	30	45 0.015	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30

Table D.2A: Water Quality Targets for Rivers in each Water Management Sub-zone* (Note: refer to Table D.4A for the water quality targets that apply to lakes)

Water Management Zone*	Sub-zone*	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	QMCI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 m	Δ	< 50 th %ile	%Δ
	Upper Tokomaru (Mana_13b)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Lower Tokomaru (Mana_13c)	7 to 8.5	0.5	24	3	70	2	5	120	30	40 0.010	444 0.444	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Mangaore (Mana_13d)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	0.167	5 100	400 0.400	2.1	95			45	30	2.5	30
	Koputaroa (Mana_13e)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
	Foxtan Loop (Mana_13f)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	444 0.444	5 100	400 0.400	2.1	95			45	30	2.5	30
Upper Rangitikei (Rang_1)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	0.6		3.5	20	3.4	20	
Middle Rangitikei (Rang_2)	Middle Rangitikei (Rang_2a)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	0.6		3.5	20	3.4	20
	Pukeokahu – Mangaweka (Rang_2b)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	110 0.110	6 120	320 0.320	1.7	99	0.6		3.5	20	3.4	20
	Upper Moawhango (Rang_2c)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Middle Moawhango (Rang_2d)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Lower Moawhango (Rang_2e)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5	20		30	2	30
	Upper Hautapu (Rang_2f)	7 to 8.5	0.5	19	2	80	4 1.5	2.5 5	120	30	40 0.010	110 0.110	6 120	400 0.400	2.1	99	4		45	20	3	20
	Lower Hautapu (Rang_2g)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5	20		30	2	30
Lower Rangitikei (Rang_3)	Lower Rangitikei (Rang_3a)	7 to 8.5	0.5	19	3	80	4 1.5	2.5 5	120	30	40 0.010	110 0.110	6 120	400 0.400	2.1	99	4		45	20	3	20
	Makohine (Rang_3b)	7 to 8.5	0.5	22	3	70	2	5	200	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95		20		30	1.6	30

Table D.2A: Water[^] Quality Targets for Rivers[^] in each Water Management Sub-zone[^] (Note: refer to Table D.4A for the water[^] quality targets that apply to lakes[^])

Water Management Zone [^]	Sub-zone [^]	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	Q _{MCI}	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 xm	Δ	< 50 th %ile	%Δ
Coastal Rangitikei (Rang_4)	Coastal Rangitikei (Rang_4a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Tidal Rangitikei (Rang_4b)	7 to 8.5	0.5	24	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Porewa (Rang_4c)	7 to 8.5	0.5	22	3	70	2	5	200 120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95		20		30	1.6	30
	Tutaenui (Rang_4d)	7 to 8.5	0.5	24	3	60	2	5	200	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95			45	30	2.5	30
Upper Whanganui (Whai_1)	Upper Whanganui (Whai_1)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
Cherry Grove (Whai_2)	Cherry Grove (Whai_2a)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Upper Whakapapa (Whai_2b)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Lower Whakapapa (Whai_2c)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Piopiotea (Whai_2d)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Pungapunga (Whai_2e)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Upper Ongarue (Whai_2f)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	2.5		5	20	3	20
	Lower Ongarue (Whai_2g)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
Te Maire (Whai_3)	Te Maire (Whai_3)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
Middle Whanganui (Whai_4)	Middle Whanganui (Whai_4a)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
	Upper Ohura (Whai_4b)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30
	Lower Ohura (Whai_4c)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30

Table D.2A: Water Quality Targets for Rivers in each Water Management Sub-zone* (Note: refer to Table D.4A for the water quality targets that apply to lakes)

Water Management Zone*	Sub-zone*	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	QMCI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chla Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 xm	Δ	< 50 th %ile	%Δ
	Retaruke (Whai_4d)	7 to 8.5	0.5	19	2	80	4 1.5	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
Pipiriki (Whai_5)	Pipiriki (Whai_5a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5	20		30	2	30
	Tangarakau (Whai_5b)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30
	Whangamomona (Whai_5c)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30
	Upper Manganui o te Ao (Whai_5d)	7 to 8.2	0.5	19	2	80	4 1.5	2.5 5	50	30	6 0.006	70 0.070	6 120	320 0.320	1.7	99	0.6		3.5	20	3.4	20
	Makatote (Whai_5e)	7 to 8.2	0.5	19	2	80	1.5	5	50		0.006	0.070	120	0.320	1.7	99					3.4	20
	Waimarino (Whai_5f)	7 to 8.2	0.5	19	2	80	1.5	5	50		0.006	0.070	120	0.320	1.7	99					3.4	20
	Middle Manganui o te Ao (Whai_5g)	7 to 8.2	0.5	19	2	80	1.5	5	50		0.006	0.070	120	0.320	1.7	99					3.4	20
	Mangaturuturu (Whai_5h)	7 to 8.2	0.5	19	2	80	1.5	5	50		0.006	0.070	120	0.320	1.7	99					3.4	20
	Lower Manganui o te Ao (Whai_5ei)	7 to 8.5	0.5	19	2	80	4 1.5	2.5 5	120	30	40 0.010	110 0.110	6 120	320 0.320	1.7	99	0.6		3.5	20	3.4	20
	Orautoha (Whai_5j)	7 to 8.5	0.5	19	2	80	1.5	5	120		0.010	0.110	120	0.320	1.7	99					3.4	20
Paetawa (Whai_6)	Paetawa (Whai_6)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5	20		30	2	30
Lower Whanganui (Whai_7)	Lower Whanganui (Whai_7a)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30
	Coastal Whanganui (Whai_7b)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30
	Upokongaro (Whai_7c)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30
	Matarawa (Whai_7d)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20		30	1.6	30

Table D.2A: Water Quality Targets for Rivers in each Water Management Sub-zone* (Note: refer to Table D.4A for the water quality targets that apply to lakes)

Water Management Zone*	Sub-zone*	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	QMCI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chla Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	< m	< 3 m	Δ	< 50 th %ile	%Δ
Upper Whangaehu (Whau_1)	Upper Whangaehu (Whau_1a)	7 to 8.2 ^(*)	0.5	19	2	80	4 <u>1.5</u>	2.5 <u>5</u>	50	30	6 <u>0.006</u>	70 <u>0.070</u>	6 <u>120</u>	320 <u>0.320</u>	1.7	99			5 ^(*)	20	3	20
	Waitangi (Whau_1b)	7 to 8.5	0.5	19	2	80	4 <u>1.5</u>	5	120	30	40 <u>0.010</u>	110 <u>0.110</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95	2.5		45	30	2.5	30
	Tokiahuru (Whau_1c)	7 to 8.2	0.5	19	2	80	4 <u>1.5</u>	2.5 <u>5</u>	50	30	6 <u>0.006</u>	70 <u>0.070</u>	6 <u>120</u>	320 <u>0.320</u>	1.7	99	2.5		5	20	3	20
Middle Whangaehu (Whau_2)	Middle Whangaehu (Whau_2)	7 to 8.5 ^(*)	0.5	22	3	70	2	5	200	30	45 <u>0.015</u>	167 <u>0.167</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95		20 ^(*)		30	1.6	30
Lower Whangaehu (Whau_3)	Lower Whangaehu (Whau_3a)	7 to 8.5 ^(*)	0.5	22	3	70	2	5	200	30	45 <u>0.015</u>	167 <u>0.167</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95		20 ^(*)		30	2	30
	Upper Makotuku (Whau_3b)	7 to 8.2	0.5	19	2	80	4 <u>1.5</u>	2.5 <u>5</u>	50	30	6 <u>0.006</u>	70 <u>0.070</u>	6 <u>120</u>	320 <u>0.320</u>	1.7	99	2.5		5	20	3	20
	Lower Makotuku (Whau_3c)	7 to 8.2	0.5	19	2	80	4 <u>1.5</u>	2.5 <u>5</u>	50	30	6 <u>0.006</u>	70 <u>0.070</u>	6 <u>120</u>	320 <u>0.320</u>	1.7	99	2.5		5	20	3	20
	Upper Mangawhero (Whau_3d)	7 to 8.2	0.5	19	2	80	4 <u>1.5</u>	2.5 <u>5</u>	50	30	6 <u>0.006</u>	70 <u>0.070</u>	6 <u>120</u>	320 <u>0.320</u>	1.7	99	2.5		5	20	3	20
	Lower Mangawhero (Whau_3e)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 <u>0.010</u>	110 <u>0.110</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95	2.5	20		30	2	30
	Makara (Whau_3f)	7 to 8.2	0.5	19	2	80	1.5	5	50		0.006	0.070	120	0.320	1.7	99					3	20
Coastal Whangaehu (Whau_4)	Coastal Whangaehu (Whau_4)	7 to 8.5 ^(*)	0.5	22	3	70	2	5	200	30	45 <u>0.015</u>	167 <u>0.167</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95		20 ^(*)		30	1.6	30
Turakina (Tura_1)	Upper Turakina (Tura_1a)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 <u>0.015</u>	167 <u>0.167</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95		20		30	1.6	30
	Lower Turakina (Tura_1b)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 <u>0.015</u>	167 <u>0.167</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95		20		30	1.6	30
	Ratana (Tura_1c)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 <u>0.015</u>	167 <u>0.167</u>	5 <u>100</u>	400 <u>0.400</u>	2.1	95		45	30	2.5	30	
Ohau (Ohau_1)	Upper Ohau (Ohau_1a)	7 to 8.2	0.5	19	2	80	4 <u>1.5</u>	2.5 <u>5</u>	50	30	6 <u>0.006</u>	70 <u>0.070</u>	6 <u>120</u>	320 <u>0.320</u>	1.7	99	2.5		5	20	3	20

Table D.2A: Water[^] Quality Targets for Rivers[^] in each Water Management Sub-zone^{*} (Note: refer to Table D.4A for the water[^] quality targets that apply to lakes[^])

Water Management Zone [*]	Sub-zone [*]	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	QMCI	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chla Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 xm	Δ	< 50 th %ile	%Δ
	Lower Ohau (Ohau_1ba)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	110 0.110	5 100	400 0.400	2.1	95	2.5		45	30	2.5	30
Owahanga (Owha_1)	Owahanga (Owha_1)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20	30	1.6	30	
East Coast (East_1)	East Coast (East_1)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20	30	1.6	30	
Akitio (Akit_1)	Upper Akitio (Akit_1a)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20	30	1.6	30	
	Lower Akitio (Akit_1b)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20	30	1.6	30	
	Waihi (Akit_1c)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20	30	1.6	30	
Northern Coastal (West_1)	Northern Coastal (West_1)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Kai Iwi (West_2)	Kai Iwi (West_2)	7 to 8.5	0.5	22	3	70	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		20	30	1.6	30	
Mowhanau (West_3)	Mowhanau (West_3)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Kaitoke Lakes (West_4)	Kaitoke Lakes (West_4)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Southern Whanganui Lakes (West_5)	Southern Whanganui Lakes (West_5)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Northern Manawatu Lakes (West_6)	Northern Manawatu Lakes (West_6)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Waitarere (West_7)	Waitarere (West_7)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Lake Papaitonga (West_8)	Lake Papaitonga (West_8)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	
Waikawa (West_9)	Waikawa (West_9a)	7 to 8.5	0.5	22	3	70	2	5	120	30	40 0.010	167 0.167	5 100	400 0.400	2.1	95		45	30	2.5	30	

Table D.2A: Water[^] Quality Targets for Rivers[^] in each Water Management Sub-zone* (Note: refer to Table D.4A for the water[^] quality targets that apply to lakes[^])

Water Management Zone [*]	Sub-zone [*]	pH		Temp (°C)		DO (%SAT)	scBOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		DRP (mg/m ³)	SIN (mg/m ³)	Q _{MCI}	Ammoniacal Nitrogen (mg/m ³)		Tox.	Turbidity (NTU)				Visual Clarity (m)	
		Range	Δ	<	Δ	>	<	<	Chl a (mg/m ²)	% cover	<	<	≥	<	Max	%	<1/2 m	<m	<3 xm	Δ	< 50 th %ile	%Δ
	Manakau (West_9b)	7 to 8.5	0.5	22	3	70	2	5	120		0.010	0.167	100	0.400	2.1	95					2.5	30
Lake Horowhenua (Hoki_1)	Lake Horowhenua (Hoki_1a)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95			45	30	2.5	30
	Hokio (Hoki_1b)	7 to 8.5	0.5	24	3	60	2	5	200	30	45 0.015	167 0.167	5 100	400 0.400	2.1	95			45	30	2.5	30

[Formerly POP at D-81 to D-87]

Additional water quality standards applying to the streams and rivers classified as Trout Spawning. The following standards apply to all streams where the TS (Trout Spawning) value is identified, from 1st May to 30 September inclusive.

1. The temperature of the water shall not be changed by more than 2°C, and
2. The temperature of the water shall not exceed 11°C, and
3. The dissolved oxygen concentration shall not be less than 80% saturation, and
4. There shall be no measurable increase in sediment or particulate organic matter deposited on the bed of the river or stream, and
5. The concentration of toxicants in the water shall not exceed the trigger values defined in the 2000 ANZECC guidelines Table 3.4.1 with the level of protection of 99 % of species.

Table D.3A: Additional Water[^] Quality Targets that apply 1 May to 30 September (inclusive) to all Specified Sites/Reaches of Rivers[^] with a Trout Spawning (TS) Value				
<u>Temp</u> (°C)		<u>DO</u> (%SAT)	<u>Sediment or POM</u>	<u>Toxicants (%)</u>
≤	Δ	≥		
11	2	80	No measurable increase of deposited sediment or particulate organic matter (POM) on the bed [^] of the river [^]	99

[Formerly POP at D-92]

Water quality standards for natural lakes and lake catchments

This part defines:

- water management subzones where water quality standards for lakes and lake catchments are defined (Table D.18); and
- water quality standard for natural lake waters, and
- water quality standard for streams and rivers that flow into lakes (Table D.19 and Table D.20)

The following zones contain natural lakes:

Table D.18: Water Management Sub-zones where lake water and lake catchment water quality standards apply

West_1	Tura_1c	Mana_13a
Whai_7b	West_5	Hoki_1a
West_4	West_6	West_8
Whau_4	West_7	

Lowland lakes water quality standards. These standards apply year round to waters of all natural lakes within the water management subzones defined in Table D18.

1. The pH of the water shall be within the range 7 to 8.5 and shall not be changed by more than 0.5 pH;
2. The temperature of the water shall not be changed by more than 1°C;
3. The Dissolved Oxygen concentration shall not be less than 80% in the surface waters (defined as less than 2 metres deep);
4. The five days Biological oxygen demand shall not exceed 1 g/m³;
5. The annual average algal biomass shall not exceed 5 mg Chlorophyll a/m³ and no sample shall exceed 15 mg Chlorophyll a/m³;
6. The annual average total phosphorus concentration shall not exceed 20 mg/m³;
7. The annual average total nitrogen concentration shall not exceed 337 mg/m³;
8. The concentration of ammoniacal Nitrogen shall not exceed 337 mg/m³;
9. For toxicants not otherwise defined in these standards, the concentration of toxicants in the water shall not exceed the trigger values defined in the 2000 ANZECC guidelines Table 3.4.1 with the level of protection of 95 % of species;
10. The clarity of the water measured as Secchi depth shall not be less than 2.8m and shall not be changed by more than 20%;
11. The turbidity shall not be changed by more than 20%. This standard shall apply only when physical conditions existing at the site prevent adequate water clarity (Secchi Disc) measurement.
12. The concentration of Escherichia coli shall not exceed 260 per 100 millilitres. This standard applies during the period 1st November to 30th April inclusive, and
13. The concentration of Escherichia coli shall not exceed 550 per 100 millilitres. This standard applies during the period 1st May to 31th October inclusive year round.
4. The concentration of toxins due to cyanobacteria (blue-green algae) shall not exceed 20 milligrams per cubic metre. This standard applies year round

Table D.19: The water quality standards defined in Table D.20 shall be read as follows (the numerical values in Table D.20 are indicated by [...])

Column		Standard spelt-out
header	sub-header	
pH	Range	The pH of the water shall be within the range [...] to [...]
	Δ	The pH of the water shall not be changed by more than
Temp (°C)	<	The temperature of the water shall not exceed [...] degrees Celsius.
	Δ	The temperature of the water shall not be changed by more than [...] degrees Celsius.
DO (%SAT)	<	The concentration of dissolved oxygen shall exceed [...] % of saturation
BOD ₅ (g/m ³)	<	The five days biological oxygen demand shall not exceed [...] grams per cubic metre.
POM (g/m ³)	<	The concentration of particulate organic matter shall not exceed [...] grams per cubic metre.
Periphyton	Chla (mg/m ²)	The algal biomass on the stream or river bed shall not exceed [...] milligrams of chlorophyll a per square metre.
	% cover	The maximum cover of visible stream or river bed by periphyton (as filamentous algae more than 2 centimetres long) shall not exceed [...] % between 1 st November to 30 th April inclusive.
TP (mg/m ³)	<	The mean monthly concentration of total phosphorus shall not exceed [...] milligrams per cubic metre, unless natural levels already exceed this standard.
TN (mg/m ³)	<	The mean monthly concentration of total nitrogen shall not exceed [...] milligrams per cubic metre.
Ammonia (mg/m ³)	<	The concentration of ammonia nitrogen reactive phosphorus shall not exceed [...] milligrams per cubic metre.
Toxicants	<	For toxicants not otherwise defined in these standards, the concentration of toxicants in the water shall not exceed the trigger values defined in the 2000 ANZECC guidelines Table 3.4.1 with the level of protection of [...] % of species.
Turbidity (NTU)	< 1/2 m	The turbidity of the water when the river flow is at or below half median flow shall not exceed [...] Nephelometric Turbidity Units (NTU)
	< m	The turbidity of the water when the river flow is at or below median flow shall not exceed [...] Nephelometric Turbidity Units (NTU)
	< 3 x m	The turbidity of the water when the river flow is at or below three times median flow shall not exceed [...] Nephelometric Turbidity Units (NTU)
	Δ	The turbidity of the water shall not be changed by more than [...] %
Clarity (m)	Δ	The clarity of the water measured as being the horizontal sighting range of a 200 mm black disc shall not be changed by more than [...] %

Notes:

- a. The pH change standard applies only within the bounds of the pH range standard
- b. The temperature change standard applies only within the bounds of the temperature standard.
- c. Soluble Inorganic Nitrogen (SIN) concentration is measured of the sum of nitrate nitrogen, nitrite nitrogen and ammonia nitrogen

Table D-20: The following water quality standards apply to streams and rivers in natural lakes catchments (i.e., flowing directly or indirectly into a natural lake)

Management Zone	Management Sub-zone	pH		Temp (°C)		DO (%SAT)	BOD ₅ (g/m ³)	POM (g/m ³)	Periphyton		TP (mg/m ³)	TN (mg/m ³)	Ammonia (mg/m ³)	Toxicants	Turbidity (NTU)				Clarity (m)
		Range	Δ	<	Δ	>	<	<	Chla (mg/m ²)	% cover	<	<	<		<1/2 m	< m	<3 xm	Δ	Δ
Coastal Manawatu Mana_13	Coastal Manawatu Mana_13a	7 to 8.5	0.5	24	3	70	2	5	200	30	20	337	337	95	2.5		45	30	30
Lower Whanganui Whai_7	Coastal Whanganui Whai_7b	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95		20		30	30
Coastal Whangaehu Whau_4	Coastal Whangaehu Whau_4	7 to 8.5	0.5	22	3	70	2	5	200	30	20	337	337	95		20		30	30
Turakina Tura_1	Ratana Tura_1e	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Northern Coastal West_1	Northern Coastal West_1	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Kaitoke Lakes West_4	Kaitoke Lakes West_4	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Southern Wanganui Lakes West_5	Southern Wanganui Lakes West_5	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Northern Manawatu Lakes West_6	Northern Manawatu Lakes West_6	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Waitarere West_7	Waitarere West_7	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Lake Papaitonga West_8	Lake Papaitonga West_8	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30
Lake Horowhenua Hoki_1	Lake Horowhenua Hoki_1a	7 to 8.5	0.5	24	3	60	2	5	200	30	20	337	337	95			45	30	30

Note these water management subzones also contain streams and river that do not flow into a natural lake. For these waters, standards in Table D.17 apply

Table D.4A: Lake[^] Water[^] Quality Targets (Note: targets apply year-round to the waters[^] of types of lakes[^] not excluded by Schedule E Table E.2(b) v to vii)

Lake Type	Algal Biomass Chl a (mg/m ³)		TP (g/m ³)	TN (g/m ³)	Ammoniacal Nitrogen (g/m ³)	Tox.	Visual Clarity (m)		Euphotic Depth	E. coli / 100 ml	
	≤	Max.	≤	≤	≤ ²	%	≥	%Δ	%Δ	Summer (1 Nov – 30 Apr)	Winter (1 May – 31 Oct)
Deep lakes (≥ 5 m deep)	5	15	0.020	0.337	0.400	95	2.8	20	10	260	550
Shallow lakes (< 5 m deep)	12	30	0.043	0.735	0.400	95	0.8	20	10	260	550

[Formerly POP at D-88 to D-89]

Water quality standards for the marine coastal waters. The following standards apply year round to the waters within the coastal Marine area.

1. The pH of the water shall be within the range 8 to 8.3 and shall not be changed by more than 0.1 pH;
2. The temperature of the water shall not be changed by more than 1°C;
3. The Dissolved Oxygen concentration shall not be less than 90 % in the surface waters defined as less than 2 metres deep;
4. The average annual algal biomass shall not exceed 1 mg Chlorophyll a/m³;
5. The average annual total phosphorus concentration shall not exceed 10 mg/m³;
6. The average annual total nitrogen concentration shall not exceed 60 mg/m³;
7. The concentration of ammonia nitrogen shall not exceed 60 mg/m³;
8. For toxicants not otherwise defined in these standards, the concentration of toxicants in the water shall not exceed the trigger values defined in the 2000 ANZECC guidelines Table 3.4.1 with the level of protection of 99 % of species;
9. The clarity of the water measured as Secchi depth shall not be changed by more than 20%;
10. The turbidity shall not be changed by more than 20%. This standard shall apply only when physical conditions existing at the site prevent adequate water clarity (Secchi Disc) measurement.
11. The concentration of *Enterococci* shall not exceed 140 per 100 millilitres. This standard applies during the period 1st November to 30th April inclusive, and
12. The concentration of *Enterococci* shall not exceed 280 per 100 millilitres. This standard applies during the period 1st May to 31th October inclusive.
13. The median concentration of faecal coliforms shall not exceed 14 per 100 millilitres and the 90th percentile shall not exceed 43 per 100 millilitres. This standard applies year round.
14. The concentration of toxins due to cyanobacteria (blue green algae) shall not exceed 20 milligrams per cubic metre. This standard applies year round.

² Target only applies when lake pH exceeds 8.5 within the epilimnion (shallow lakes) or within 2 m of the water surface (deep lakes)

Table D.16: The Water quality standards defined in Table 2 shall be read as follows (The numerical values in are indicated by [...])

Table D.5A: Water^A Quality Targets Key: Definition of abbreviations and full wording of the targets (placement of the numerical values for a specified target are indicated by [...])		
Column Header	Abbreviations used in Tables D.1A to D.4A	Standard spell-out Full Wording of the Target
Header	Sub-header	
pH	Range	The pH of the water ^A must be within the range [...] to [...] unless natural levels are already outside this range.
	Δ	The pH of the water ^A must not be changed by more than [...].
Temp (°C)	<	The temperature of the water ^A must not exceed [...] degrees Celsius.
	Δ	The temperature of the water ^A must not be changed by more than [...] degrees Celsius.
DO (% SAT)	< >	The concentration of dissolved oxygen (DO) must exceed [...] % of saturation.
sCBOD ₅ (g/m ³)	<	The monthly average five-days filtered / soluble carbonaceous biological oxygen demand (sCBOD ₅) when the river ^A flow is at or below the 20 th flow exceedance percentile* must shall not exceed [...] grams per cubic metre.
POM (g/m ³)	<	The average concentration of particulate organic matter when the river ^A flow is at or below the 50 th flow exceedance percentile* must shall not exceed [...] grams per cubic metre.
Periphyton (rivers ^A)	Chl a Chl a (mg/m ²)	The algal biomass on the stream or river ^A bed ^A must shall not exceed [...] milligrams of chlorophyll a per square metre.
	% cover	The maximum cover of visible river ^A bed ^A by periphyton (as filamentous algae more than 2 centimetres long) must shall not exceed [...] %. The maximum cover of visible river bed by periphyton as diatoms or cyanobacteria more than 0.3 centimetres thick must not exceed [...] %.
Algal biomass Chl a (mg/m ³) (lakes ^A)	≤	The annual average algal biomass must not exceed [...] milligrams chlorophyll a per cubic metre.
	Maximum	Samples must not exceed [...] milligrams chlorophyll a per cubic metre.
DRP (mg/m ³)	<	The annual average concentration of dissolved reactive phosphorus (DRP) when the river ^A flow is at or below three times the median 20 th flow exceedance percentile* flow must shall not exceed [...] milligrams per cubic metre, unless natural levels already exceed this target standard.
TP (g/m ³) (lakes ^A)	≤	The annual average concentration of total phosphorus (TP) must not exceed [...] milligrams per cubic metre.
SIN (mg/m ³)	<	The annual average concentration of soluble inorganic nitrogen (SIN) ³ when the river ^A flow is at or below the three times the median 20 th flow exceedance percentile* flow must shall not exceed [...] milligrams per cubic metre, unless natural levels already exceed this target.
TN (g/m ³) (lakes ^A)	≤	The annual average concentration of total nitrogen must not exceed [...] milligrams per cubic metre.
QMCI ⁴	≥	The quantitative Macroinvertebrate Community Index (MCI) must shall exceed [...], unless natural physical conditions are beyond the scope of application of the QMCI. In cases where the river ^A habitat is suitable for the application of the soft-bottomed variant of the MCI (sb-MCI) the targets also apply.
QMCI	% Δ	There must be no more than a 20 % reduction in Quantitative Macroinvertebrate Community Index (QMCI) score between appropriately matched habitats upstream and downstream of discharges to water ^A .
Ammoniacal nitrogen ⁵ (mg/m ³) (rivers ^A)	<	The average concentration of ammoniacal nitrogen must shall not exceed [...] milligrams per cubic metre.
	Max	The maximum concentration of ammoniacal nitrogen must not exceed [...] grams per cubic metre.
Ammoniacal nitrogen (g/m ³) (lakes ^A)	≤	The concentration of ammoniacal nitrogen must not exceed [...] grams per cubic metre when lake ^A pH exceeds 8.5 within the epilimnion (shallow lakes ^A) or within 2 m of the water ^A surface (deep lakes ^A).
Tox. or Toxicants	< %	For toxicants not otherwise defined in these targets standards, the concentration of toxicants in the water ^A must shall not exceed the trigger values for freshwater defined in the 2000 ANZECC guidelines Table 3.4.1 for the level of protection of [...] % of species. For metals the trigger value must be adjusted for hardness and apply to the dissolved fraction as directed in the table.
Turbidity (NTU)	< 1/2 m	The turbidity of the water when the river flow is at or below half median flow shall not exceed [...] Nephelometric Turbidity Units (NTU)
	< m	The turbidity of the water when the river flow is at or below median flow shall not exceed [...] Nephelometric Turbidity Units (NTU)
	< 3 x m	The turbidity of the water when the river flow is at or below three times median flow shall not exceed [...] Nephelometric Turbidity Units (NTU)
	Δ	The turbidity of the water shall not be changed by more than [...] %. This standard shall apply only when physical conditions existing at the site prevent adequate water clarity (back Disc) measurement.
Visual Clarity (m) (rivers ^A)	% Δ	The visual clarity of the water ^A measured as being the horizontal sighting range of a 200-mm black disc must shall not be changed reduced by more than [...] %.
	≥	The visual clarity of the water ^A measured as the horizontal sighting range of a black disc must equal or exceed [...] metres when the river ^A is at or below the 50 th flow exceedance percentile*.
Visual Clarity (m) (lakes ^A)	% Δ	The visual clarity of the water ^A measured as the horizontal sighting range of a black disc must not be reduced by more than [...] %.
	≥	The visual clarity of the water ^A measured as the horizontal sighting range of a black disc must equal or exceed [...] metres.
E. coli / 100 ml (rivers ^A)	≤ m	The concentration of <i>Escherichia coli</i> must not exceed [...] per 100 millilitres 1 November - 30 April (inclusive) when the river ^A flow is at or below the 50 th flow exceedance percentile*.
	< 20 th %ile	The concentration of <i>Escherichia coli</i> must not exceed [...] per 100 millilitres year round when the river ^A flow is at or below the 20 th flow exceedance percentile*.
E. coli / 100 ml (lakes ^A)	Summer	The concentration of <i>Escherichia coli</i> must not exceed [...] per 100 millilitres 1 November - 30 April (inclusive).
	Winter	The concentration of <i>Escherichia coli</i> must not exceed [...] per 100 millilitres 1 May - 31 October (inclusive).
Euphotic Depth (lakes ^A)	% Δ	Euphotic depth must not be reduced by more than [...] %.

Notes:

d. Soluble Inorganic Nitrogen (SIN) concentration is measured of the sum of nitrate nitrogen, nitrite nitrogen and ammonia nitrogen

³ Soluble inorganic nitrogen (SIN) concentration is measured as the sum of nitrate nitrogen, nitrite nitrogen, and ammoniacal nitrogen or the sum of total oxidised nitrogen and ammoniacal nitrogen.

⁴ The Macroinvertebrate Community Index (MCI) target applies only for State of the Environment monitoring purposes to determine if the aquatic macroinvertebrate communities are adequate to provide for and maintain the values in each WMSZ. This target is not appropriate for monitoring the effect of activities such as discharges to water on macroinvertebrate communities upstream and downstream of the activity.

⁵ Ammoniacal nitrogen is a component of SIN. SIN target should also be considered when assessing ammoniacal nitrogen concentrations against the targets.

